Safety Data Sheet AWLCARE

Sales

Order: {SalesOrd}

Bulk Sales Reference No.: O73240 SDS Revision Date: 12/08/2014 SDS Revision Number: 0-2



1. Identification of the preparation and company

1.1. Product identifier

Product Identity AWLCARE
Bulk Sales Reference No. 073240

1.2. Relevant identified uses of the substance or mixture and uses advised against
 Intended Use
 Application Method
 See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name Akzo Nobel Coatings

International Paint LLC 2270 Morris Avenue P. O. Box 386

Emergency

 CHEMTREC (USA)
 (800) 424-9300

 International Paint
 (713) 527-3887

 Poison Control Center
 (800) 854-6813

Customer Service

International Paint (800) 589-1267 Fax No. (800) 631-7481

2. Hazard identification of the product

2.1. Classification of the substance or mixture

Flam. Liq. 3;H226 Flammable liquid and vapor.

2.2. Label elements

Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.



Warning.

H226 Flammable liquid and vapor.

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P260 Do not breathe mist / vapors / spray.

P262 Do not get in eyes, on skin, or on clothing.

P280 Wear protective gloves / eye protection / face protection.

P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

 $P303+361+353 \ IF \ ON \ SKIN \ (or \ hair): Remove/Take \ off immediately \ all \ contaminated \ clothing. \ Rinse \ skin \ with \ water/shower.$

P331 Do NOT induce vomiting.

P370 In case of fire: Use water spray, fog, or regular foam..

P403+233 Store in a well ventilated place. Keep container tightly closed.

P501 Dispose of contents / container in accordance with local / national regulations.

HMIS Rating Health: 2 Flammability: 2 Reactivity: 0

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

| Ingredient/Chemical Designations | Weight % | GHS Classification | Notes |
|--|----------|--------------------|--------|
| Stoddard solvent CAS Number: 0008052-41-3 | | Asp. Tox. 1;H304 | [1][2] |
| Dipropylene glycol monomethyl ether CAS Number: 0034590-94-8 | | | [1][2] |

- [1] Substance classified with a health or environmental hazard.
- [2] Substance with a workplace exposure limit.
- [3] PBT-substance or vPvB-substance.

4. First aid measures

4.1. Description of first aid measures

General Remove contaminated clothing and shoes. Get medical attention immediately. Wash

clothing before reuse. Thoroughly clean or destroy contaminated shoes.

Inhalation If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. Get medical attention immediately.

Eyes In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.

Get medical attention immediately.

Skin In case of contact, immediately flush skin with soap and plenty of water. Get medical

attention immediately.

Ingestion If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT

induce vomiting unless instructed to do so by medical personnel. Never give anything

by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

Overview NOTICE: Reports have associated repeated and prolonged occupational

overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be

harmful or fatal. Avoid contact with eyes, skin and clothing.

Inhalation Harmful if inhaled. Causes lung irritation. Causes nose and throat irritation. Vapors

may affect the brain or nervous system causing dizziness, headache or nausea.

Eyes Causes severe eye irritation. Avoid contact with eyes.

Skin Causes skin irritation. May be harmful if absorbed through the skin.

Ingestion Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or

drowsiness.

Chronic effects Cancer hazard. Contains an ingredient which can cause cancer (See Section 2 and

Section 15 for each ingredient). Risk of cancer depends on duration and level of

exposure.

5. Fire-fighting measures

5.1. Extinguishing media

CAUTION: This product has a very low flashpoint. Use of water spray when fighting fire may be inefficient. CAUTION: For mixtures containing alcohol or polar solvent, alcohol-resistant foam may be more effective. SMALL FIRES: Use dry chemical, CO2, water spray or regular foam. LARGE FIRES: Use water spray, fog, or regular foam. Do not use straight streams. Move containers from fire area if you can do so without risk.

5.2. Special hazards arising from the substance or mixture

HIGHLY FLAMMABLE MATERIALS: Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier

^{*}The full texts of the phrases are shown in Section 16.

than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks) creating a vapor explosion hazard. Runoff to sewers may create fire or explosion hazard. Containers may explode when heated. Many liquids are lighter than water.

5.3. Advice for fire-fighters

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses.

ERG Guide No. 128

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.

6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

6.3. Methods and material for containment and cleaning up

CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 50 meters (150 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet).

7. Handling and storage

7.1. Precautions for safe handling

Handling

Vapors may cause flash fire or ignite explosively.

In Storage

Keep away from heat, sparks and flame.

7.2. Conditions for safe storage, including any incompatibilities

Store between 40-100F (4-38C).

Avoid contact with eyes, skin and clothing.

Strong oxidizing agents.

Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone.

7.3. Specific end use(s)

Close container after each use.

Wash thoroughly after handling.

Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

8. Exposure controls and personal protection

8.1. Control parameters

Exposure

| CAS No. | Ingredient | Source | Value |
|--------------|------------------|--------------|---|
| 0008052-41-3 | Stoddard solvent | OSHA | 500 ppm TWA; 2900 mg/m3 TWA |
| | | ACGIH | 100 ppm TWA |
| | | NIOSH | 350 mg/m3 TWA1800 mg/m3 Ceiling (15 min)20000 mg/m3 IDLH |
| | | Supplier | |
| | | OHSA, CAN | 525 mg/m3 TWA (140C Flash aliphatic solvent) |
| | | Mexico | 100 ppm TWA LMPE-PPT; 523 mg/m3 TWA LMPE-PPT200 ppm STEL [LMPE-CT]; 1050 mg/m3 |

| | | STEL [LMPE-CT] |
|--|--------------|---|
| | Brazil | |
| Dipropylene glycol monomethyl ether | OSHA | 100 ppm TWA; 600 mg/m3 TWA150 ppm STEL; 900 mg/m3 STEL |
| | ACGIH | 100 ppm TWA150 ppm STEL |
| | NIOSH | 100 ppm TWA; 600 mg/m3 TWA150 ppm STEL; 900 mg/m3 STEL600 ppm IDLH |
| | Supplier | |
| | OHSA, CAN | 100 ppm TWA150 ppm STEL |
| | Mexico | 100 ppm TWA LMPE-PPT; 60 mg/m3 TWA LMPE-PPT150 ppm STEL [LMPE-CT]; 900 mg/m3 STEL [LMPE-CT] |
| | Brazil | |

Health Data

| | 11041111 2414 | | | | |
|--------------|-------------------------------------|--------|---|--|--|
| CAS No. | Ingredient | Source | Value | | |
| 0008052-41-3 | Stoddard solvent | NIOSH | Eye nose | | |
| 0034590-94-8 | Dipropylene glycol monomethyl ether | | Narcotic effects mild irritation of the nose and eyes | | |

Carcinogen Data

| CAS No. | Ingredient | Source | Value |
|--------------|--------------------|--------|--|
| 0008052-41-3 | Stoddard solvent | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0034590-94-8 | Dipropylene glycol | OSHA | Select Carcinogen: No |
| | monomethyl ether | NTP | Known: No; Suspected: No |
| | | | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |

8.2. Exposure controls

Respiratory

Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.

Eyes

Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.

Skin

Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.

Engineering Controls
Other Work Practices

Depending on the site-specific conditions of use, provide adequate ventilation. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.

9. Physical and chemical properties

Appearance Coloured Liquid
Odour threshold Not Measured

pH ?

 $\begin{array}{lll} \mbox{Melting point } & \mbox{Not Measured} \\ \mbox{Initial boiling point and boiling range} & 188 \ (^{\circ}\mbox{C}) \ \ 370 \ \ (^{\circ}\mbox{F}) \\ \mbox{Flash Point} & 42 \ \ (^{\circ}\mbox{C}) \ \ 108 \ \ \ (^{\circ}\mbox{F}) \\ \mbox{Evaporation rate (Ether = 1)} & \mbox{Not Measured} \\ \mbox{Flammability (solid, gas)} & \mbox{Not Applicable} \end{array}$

Upper/lower flammability or explosive

limits

Lower Explosive Limit: 1

Upper Explosive Limit: No Established Limit

vapor pressure (Pa) Not Measured
Vapor Density Heavier than air

Specific Gravity 0.81

Partition coefficient n-octanol/water (Log

Kow)
Auto-ignition temperature
Decomposition temperature
Not Measured
Not Measured

Viscosity (cSt)

No Established Limit Not Measured

VOC % Refer to the Technical Data Sheet or label where information is

Not Measured

available.

10. Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

HIGHLY FLAMMABLE MATERIALS: Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks) creating a vapor explosion hazard. Runoff to sewers may create fire or explosion hazard. Containers may explode when heated. Many liquids are lighter than water.

11. Toxicological information

Acute toxicity

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

| Ingredient | Oral LD50, mg/kg | Skin LD50, mg/kg | Inhalation Vapor LD50, mg/L/4hr | Inhalation Dust/Mist LD50, mg/L/4hr |
|--|--------------------------------|--|---------------------------------------|---|
| Stoddard solvent - (8052-41-3) | No data available | No data available | No data available | No data available |
| Dipropylene glycol monomethyl ether - (34590-94-8) | 3,500.00, Rat - Category: 5 | 19,000.00, Rabbit - Category: NA | No data available | No data available |

| Item | Category | Hazard |
|------|----------|--------|

| Acute Toxicity (mouth) | Not Classified | Not Applicable |
|---|----------------|----------------|
| Acute Toxicity (skin) | Not Classified | Not Applicable |
| Acute Toxicity (inhalation) | Not Classified | Not Applicable |
| Skin corrosion/irritation | Not Classified | Not Applicable |
| Eye damage/irritation | Not Classified | Not Applicable |
| Sensitization (respiratory) | Not Classified | Not Applicable |
| Sensitization (skin) | Not Classified | Not Applicable |
| Germ toxicity | Not Classified | Not Applicable |
| Carcinogenicity | Not Classified | Not Applicable |
| Reproductive Toxicity | Not Classified | Not Applicable |
| Specific target organ systemic toxicity (single exposure) | Not Classified | Not Applicable |
| Specific target organ systemic Toxicity (repeated exposure) | Not Classified | Not Applicable |
| Aspiration hazard | Not Classified | Not Applicable |

12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

| Ingredient | 96 hr LC50 fish, mg/l | 48 hr EC50 crustacea, mg/l | ErC50 algae, mg/l |
|--|--------------------------------|-------------------------------|-----------------------|
| Stoddard solvent - (8052-41-3) | Not Available | Not Available | Not Available |
| Dipropylene glycol monomethyl ether - (34590-94-8) | 10,000.00, Pimephales promelas | 1,919.00, Daphnia magna | 969.00 (72 hr), Algae |

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available

13. Disposal considerations

13.1. Waste treatment methods

Do not allow spills to enter drains or watercourses.

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transport information

14.1. UN number UN 126314.2. UN proper shipping name PAINT

14.3. Transport hazard class(es)

DOT (Domestic Surface Transportation)

IMO / IMDG (Ocean Transportation)

DOT Proper Shipping PAINT IMDG Proper PAINT

Name Shipping Name

DOT Hazard Class 3 IMDG Hazard Class 3 Sub Class 3

UN / NA Number UN 1263

DOT Packing Group III IMDG Packing Group III CERCLA/DOT RQ Not Applicable gal. / System Reference 2

Not Applicable lbs. Code

14.4. Packing group III

14.5. Environmental hazards

IMDG Marine Pollutant: No

14.6. Special precautions for user

Not Applicable

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected

regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA

Inventory.

WHMIS Classification B3

DOT Marine Pollutants (10%):

(No Product Ingredients Listed)

DOT Severe Marine Pollutants (1%):

(No Product Ingredients Listed)

EPCRA 311/312 Chemicals and RQs (>.1%):

(No Product Ingredients Listed)

EPCRA 302 Extremely Hazardous (>.1%):

(No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals (>.1%):

(No Product Ingredients Listed)

Mass RTK Substances (>1%):

Dipropylene glycol monomethyl ether

Stoddard solvent

Penn RTK Substances (>1%):

Dipropylene glycol monomethyl ether

Stoddard solvent

Penn Special Hazardous Substances (>.01%):

No Product Ingredients Listed)

RCRA Status:

(No Product Ingredients Listed)

N.J. RTK Substances (>1%):

Dipropylene glycol monomethyl ether

Stoddard solvent

N.J. Special Hazardous Substances (>.01%):

(No Product Ingredients Listed)

N.J. Env. Hazardous Substances (>.1%):

(No Product Ingredients Listed)

Proposition 65 - Carcinogens (>0%):

(No Product Ingredients Listed)

Proposition 65 - Female Repro Toxins (>0%):

(No Product Ingredients Listed)

Proposition 65 - Male Repro Toxins (>0%):

(No Product Ingredients Listed)

Proposition 65 - Developmental Toxins (>0%):

(No Product Ingredients Listed)

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H304 May be fatal if swallowed and enters airways.

This is the first revision of this SDS format, changes from previous revision not applicable.

End of Document