

# CR Series Refrigerators/Freezers

## For Your Galley or Cockpit



CR-1080E-S shown  
without flange



**Luxury meets performance and top-of-the-line technology with Dometic's CR Series of premium refrigerators with freezer compartments.** CR refrigerator/freezers are constructed for the rigors of marine use, but designed to compliment any galley or cockpit.

Each CR Series appliance is equipped with a premium Danfoss DC compressor, providing excellent cooling performance, ultra-quiet operation, and minimal power consumption whether operating on DC or AC power. During rough sea conditions, the door remains securely closed—at top and bottom—as a result of the patented double-lock mechanism. The CR's vent mechanism holds the door open slightly for easy defrosting and mildew prevention. The door can be set to open to the left or right to accommodate any galley configuration.



### Award Winning Design

"Beyond pleasing aesthetics, the CR Series compressor refrigerators offer several clever design touches, including a lock to allow the cabinet to ventilate when not in use and a very positive latching mechanism."

—As commented by the awards jury at METS Amsterdam, the world's leading trade show for marine equipment

### Key Benefits

- 12/24 volts DC; 110/220 volts AC.
- Exclusive protected evaporator eliminates the risk of ice-pick damage.
- Cool-blue interior light.
- Diagnostic circuitry installed with green and red LED indicator lights.
- Face panel is interchangeable—even while installed in the boat.
- Four sizes and many colors to choose from.
- Recessed handle provides a smooth, sleek surface.
- Full-width freezer compartment.
- Features include egg tray, bottle holder, extra-large vegetable bin, and adjustable shelves and racks.

# Specification Details for CR Series Refrigerators/Freezers

Model	CR-1050	CR-1065	CR-1080	CR-1110
Freezer Gross Capacity	4.8 quarts (4.5 liters)	4.8 quarts (4.5 liters)	4.8 quarts (4.5 liters)	8.9 quarts (8.4 liters)
Refrigerator Gross Capacity	1.7 cu ft (48.1 liters)	2.3 cu ft (65.1 liters)	2.8 cu ft (79.1 liters)	3.8 cu ft (107 liters)
Voltage	12/24V DC (110/220V AC)	12/24V DC (110/220V AC)	12/24V DC (110/220V AC)	12/24V DC (110/220V AC)
Avg. Power Consumption	40 watts (3.3 amps)	40 watts (3.3 amps)	40 watts (3.3 amps)	45 watts (3.75 amps)
Insulation	CFC-free polyurethane	CFC-free polyurethane	CFC-free polyurethane	CFC-free polyurethane
Compressor	Danfoss BD35F	Danfoss BD35F	Danfoss BD35F	Danfoss BD35F
Refrigerant	Environmentally safe R-134A	Environmentally safe R-134A	Environmentally safe R-134A	Environmentally safe R-134A
Material	Stainless-steel fittings, plastic interior, door frame in plastic body with coated-metal frame	Stainless-steel fittings, plastic interior, door frame in plastic body with coated-metal frame	Stainless-steel fittings, plastic interior, door frame in plastic body with coated-metal frame	Stainless-steel fittings, plastic interior, door frame in plastic body with coated-metal frame
Color Options	<b>CR-1050U/F:</b> black face panel, black door surround, black flush-mount flange <b>CR-1050E/F-W:</b> white face panel, silver door surround, silver flush-mount flange <b>CR-1050E/F-S:</b> stainless-steel face panel, silver door surround, silver flush-mount flange	<b>CR-1065U/F:</b> black face panel, black door surround, black flush-mount flange <b>CR-1065E/F-W:</b> white face panel, silver door surround, silver flush-mount flange <b>CR-1065E/F-S:</b> stainless-steel face panel, silver door surround, silver flush-mount flange	<b>CR-1080U/F:</b> black face panel, black door surround, black flush-mount flange <b>CR-1080E/F-S:</b> stainless-steel face panel, silver door surround, silver flush-mount flange	<b>CR-1110U/F:</b> black face panel, black door surround, black flush-mount flange <b>CR-1110E/F-S:</b> stainless-steel face panel, silver door surround, silver flush-mount flange
*Cut-Out Dimensions with flush-mount flange	16.1" W x 21.3" H x 19.6" D (408mm x 542mm x 497mm)	18.8" W x 21.1" H x 21.3" D (478mm x 537mm x 542mm)	19.9" W x 25.6" H x 20.9" D (505mm x 649mm x 530mm)	21.6" W x 29.8" H x 22.1" D (548mm x 756mm x 560mm)
*Cut-Out Dimensions with space-saver flange	15.1" W x 21.0" H x 17.7" D (383mm x 532mm x 450mm)	17.9" W x 21.1" H x 19.4" D (454mm x 535mm x 494mm)	18.9" W x 25.5" H x 19.0" D (481mm x 648mm x 481mm)	20.6" W x 29.7" H x 20.1" D (523mm x 755mm x 511mm)
Net Weight	42 lbs (19 kg)	46 lbs (20 kg)	52 lbs (23 kg)	62 lbs (28 kg)
Flange Options	EST-0050U: black space-saver EST-0050E: silver space-saver	EST-0065U: black space-saver EST-0065E: silver space-saver	EST-0080U: black space-saver EST-0080E: silver space-saver	EST-0110U: black space-saver EST-0110E: silver space-saver
Replacement Flange Options	EFM-0050U: black flush-mt EFM-0050E: silver flush-mt	EFM-0065U: black flush-mt EFM-0065E: silver flush-mt	EFM-0080U: black flush-mt EFM-0080E: silver flush-mt	EFM-0110U: black flush-mt EFM-0110E: silver flush-mt



■ Premium cooling technology in an elegant design.



■ Patented double-lock door mechanism (indicated by white arrows).



■ Full-length recessed door handle provides comfortable opening and closing.



■ Freezer compartment with door.

## DOMETIC MARINE DIVISION

2000 N. Andrews Ave. Ext. I Pompano Beach, FL 33069 USA | 954-973-2477 | Fax 954-979-4414  
www.DometicUSA.com | MarineSales@DometicUSA.com

### 24/7 Tech Support for United States & Canada:

8:00 AM to 5:00 PM Eastern Time: 800-542-2477  
After hours and weekends: 888-440-4494

### International Sales & Service:

Europe & the Middle East: Call +44(0)870-330-6101  
For all other areas visit our website to find your nearest distributor.



Dealer: