





Flush-mounted below deck or behind wall (Max deck/wall thickness: 3/4 in)

- Sleek low-profile cover plate available in black or white Delrin
- Removable, rugged aluminum handle
- Handle can be positioned in 12 different orientations relative to pump ports
- Accommodates 1/2" 1-1/4" hose
- 10 GPM
- Ideal for use as bilge pump

Specifications / Options

Body & Ports *	Delrin / Gray
Clamp Ring	Delrin
Handle	Aluminum: Vertical (Removable)/ Silver
Valves *	Flapper, Duckbill, Umbrella
Diaphragm *	Buna-N, Buna-N Double Sided, Neoprene, Viton, EPDM, Silicone
Clevis/Button Assembly *	Delrin
Acutator	Aluminum, Stainless steel

^{*} In contact with fluid

Performance

Flow Rate Per minute¹: 10 Gal (37.9L)
Per stroke: 0.44 Qt (0.42L)
12 ft (3.7 m)
22 ft (6.7 m) with check valve
30 ft (9.1 m)


Max Pressure
Max Service
Temp
Per minute¹: 10 Gal (37.9L)
12 ft (3.7 m)
12 ft (3.7 m)
15 psi (1.0 kg/cm²)
150°F (66°C)

Available Ports

in	1/2	3/4	1	1-1/8	1-1/4
cm	1.27	1.91	2.54	2.86	3.18
Hose (Smooth)		•	s	•	•
NPT Female (Tapped)	•	•			
NPT Male (Threaded)		•	•		
Male Garden Hose (Threaded)		•			
Barbed		•		•	
Female Garden Hose Adapter		•			

S Standard • Optional

Valve Options



Removable Handle and Trim Ring Options



Top view of closed Trim Ring and Removable Handle



Black Trim Ring




White Trim Ring


Guzzler® Hand Pump GH-M400D



Pump shown mounted to plexiglass plate with white trim ring visible above mounting surface







IX.		
	in	cm
Α	9-1/2	24.1
В	4-1/2	11.4
С	12	30.5
D	13-7/8	35.2
E	10-1/4	26.0
F	5	12.7
G	4-1/2	11.4
Н	10-1/4	26.0
J	3-3/16	8.1
K	2-7/8	7.3
Mounting Holes	1/4	0.64
Weight	2 45 lb	1 11 ka

930 Waterman Avenue
East Providence, RI 02914
(401) 438-1110 • fax (401) 438-2713
toll-free (888) 438-1110 • www.thebosworthco.com

Guzzler® and Sea-lect® are trademarks of The Bosworth Company.









^{1:} at 90 cpm

Guzzler® Hand Pump GH-M400D



Example: GH-M400D-411-87-5050-00

- Guzzler Hand Pump
- Model style #M400D: Delrin Body, Flush mount, Opposite Side Ports
- Removable Vertical Handle (Silver)
- Buna-N Flapper Valves
- Buna Diaphragm
- Stainless Steel Actuator
- White Cover Plate
- Inlet: 1" Smooth
- Outlet: 1" Smooth
- No Spring



