# IDEMITSU

# SAFETY DATA SHEET

**Product Name:** 

Honda Marine Genuine Gear Case Oil 80W90, 12 x 1 Quart Case

Ø







Revision Date: 02-Jun-2017 Revision Number: 1

# IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1 Product Identifier

**Product Name:** Honda Marine Genuine Gear Case Oil 80W90, 12 x 1 Quart

Case

Other means of identification

**Product Code:** 34055057-75000C020

Synonyms Not available

1.2 Recommended use of the chemical and restrictions on use

Recommended Use Lubricant

Uses advised against No information available

1.3. Details of the supplier of the safety data sheet

Manufactured by Idemitsu Lubricants America Corporation, 701 Port Rd.,

Jeffersonville, IN. 47130 Telephone: 812-285-8234, Fax: 812-285-8243, Contact Name: Robin Hutchens, Email:

sds@ilacorp.com

**24 Hour Emergency Phone Number:** Within USA and Canada: 1 800-424-9300

Outside USA and Canada: + 1 703-741-5970 (collect calls

accepted)

# 2. HAZARDS IDENTIFICATION

#### 2.1 Classification

This material is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) and WHMIS

Acute toxicity - Oral	Not classified
Acute toxicity - Dermal	Not classified
Acute Toxicity - Inhalation (Gases)	Not classified
Acute Toxicity - Inhalation (Vapors)	Not classified
Acute Toxicity - Inhalation (Dusts/Mists)	Not classified
Skin corrosion/irritation	Not classified
Serious eye damage/eye irritation	Not classified
Respiratory sensitization	Not classified
Skin sensitization	Category 1
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
Specific target organ toxicity (single exposure)	Not classified
Specific target organ toxicity (repeated exposure)	Not classified
Aspiration toxicity	Not classified
Physical Hazards	Not classified
Physical Hazards	None

# 2.2. Label elements



Signal word

**Hazard statements** H317 - May cause an allergic skin reaction **Precautionary Statements - Prevention:** P261 - Avoid breathing dust, fume, gas, mist, vapors or spray

P280 - Wear protective gloves

P272 - Contaminated work clothing should not be allowed out of the workplace

Revision Date: 02-Jun-2017

Warning

P321 - Specific treatment (see supplemental first aid instructions **Precautionary Statements - Response:** 

on this label)

P362 + P364 - Take off all contaminated clothing and wash it

before reuse

Skin P302 + 352 - IF ON SKIN: Wash with plenty of soap and water

P363 - Wash contaminated clothing before reuse

P333 + P313 - If skin irritation or rash occurs: Get medical

advice/attention

**Precautionary Statements - Disposal:** P501 - Dispose of contents/ container to an approved waste

disposal plant

Hazards not otherwise classified (HNOC) Not applicable

#### 2.3 Other information

Other hazards • May be harmful in contact with skin

Unknown acute toxicity 9.50 % of the mixture consists of ingredient(s) of unknown toxicity

#### COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 Substances

Not applicable

#### 3.2 Mixtures

**Hazardous Components** 

Chemical Name	CAS No.	Weight-%	US GHS Classification	Notes
Olefin sulfide	68937-96-2	1-5	Skin Sens. 1 (H317) Aquatic Chronic 3 (H412)	
Phosphoric acid esters/amine salt	Confidential	1-5	Skin Sens. 1B (H317)	

**Non-Hazardous Components** 

Chemical Name	CAS No.	Weight-%
Lubricating Base Stocks	Mixture	75-85
Synthetic Lubricant	Mixture	5 - 15

# 4. FIRST AID MEASURES

#### 4.1 4.1 First Aid Measures

General Advice If symptoms persist, call a physician. Take a copy of the Safety Data Sheet when going for

medical treatment.

Eye Contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If eye irritation

persists: Get medical advice/attention.

**Skin Contact** Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. Wash contaminated clothing before re-use. Call a physician

immediately.

**Inhalation** Move to fresh air in case of accidental inhalation of vapors. If breathing is difficult, give

oxygen. If not breathing, give artificial respiration. Call a physician immediately.

**Ingestion** Do not induce vomiting without medical advice. If vomiting occurs naturally, have casualty

lean forward to reduce the risk of aspiration. If symptoms persist, call a physician.

# 4.2 4.2 Most important symptoms and effects, both acute and delayed

**Symptoms** No information available.

## 4.3 Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

# 5. FIRE-FIGHTING MEASURES

Flammable Properties NFPA: Class IIIB Combustible Liquid

5.1 Suitable Extinguishing Media:

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment

**Unsuitable Extinguishing Media:** Do not use a solid water stream as it may scatter and spread fire.

5.2 Specific Hazards Arising from the Chemical Keep product and empty container away from heat and sources

of ignition.

Hazardous combustion products: During a fire, smoke may contain the original material in addition

to combustion products of varying composition which may be toxic and / or irritating. Combustion products may include and

Revision Date: 02-Jun-2017

are not limited to: Carbon oxides Nitrogen oxides (NOx) Oxides of Phosphorus Sulphur oxides

**5.3 Protective Equipment and Precautions for Firefighters** 

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and

full protective gear.

#### 6. ACCIDENTAL RELEASE MEASURES

# 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists. Use personal

protection recommended in Section 8. Ensure adequate ventilation. Remove all sources of

ignition.

**6.2 Environmental Precautions** 

**Environmental Precautions** See section 12 for additional ecological information. Prevent further leakage or spillage if

safe to do so. Prevent product from entering drains. Do not allow material to contaminate ground water system. Do not flush into surface water or sanitary sewer system. Large Spills: Dike far ahead of liquid spill for later recovery and disposal. Prevent entry into

waterways, sewers, basements or confined areas.

6.3 Methods and material for containment and cleaning up

Methods for Clean-up Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth,

diatomaceus earth, vermiculite) and place in container for disposal according to local /

national regulations (see section 13).

Spill Management

**LARGE SPILLS** Eliminate sources of ignition. Prevent additional discharge of material if possible to do so

without hazard. For small spills implement cleanup procedures; for large spills implement cleanup procedures and, if in public area, keep public away and advise authorities. Also, if this product is subject to CERCLA reporting (see Section 15 Regulatory Information) notify

the National Response Center.

WATER SPILLS Prevent liquid entering sewers, watercourses, or low areas. Contain spilled liquid with sand

or earth. Recover by pumping or with suitable absorbent. If liquid is too viscous for pumping, scrape up. Consult an expert on disposal of recovered material and ensure

conformity to local disposal regulations.

# 7. HANDLING AND STORAGE

#### 7.1. Precautions for safe handling

**Handling** Do not breathe dusts or mists. Avoid contact with eyes, skin and

clothing. Wear protective gloves/protective clothing/eye

protection/face protection. Use personal protection recommended in Section 8. Wash hands thoroughly after handling. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. Should not be released into the

Revision Date: 02-Jun-2017

environment.

Safe Handling Advice Wear personal protective equipment. Do not breathe vapors or

spray mist. Use product only in closed system.

7.2. Conditions for safe storage, including any incompatibilities

Storage Keep in properly labeled containers. Keep container tightly closed

in a dry and well-ventilated place.

**Technical measures/Precautions** Ensure adequate ventilation. To avoid ignition of vapors by static

electricity discharge, all metal parts of the equipment must be

grounded.

Incompatible Materials and/or Coatings

No information available

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters

<u>Exposure Guidelines</u>

This product does not contain any hazardous materials with occupational exposure limits

established by the region specific regulatory bodies.

Other Exposure Guidelines (If Generated)

Other Exposure Ouldennes (II	<del>oonoratoa,</del>						
Chemical Name	OSHA PEL	ACGIH TLV	ACGIH OEL (STEL)	NIOSHT REL TWA	ILA IHG	ILA ROEG	ILA Internal Exposure Limit
Oil mist, mineral	TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>		TWA 5 mg/m <sup>3</sup> ST 10 mg/m <sup>3</sup>			

#### 8.2 Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

# **Personal Protective Equipment**

34055057-75000C020 - Honda Marine Genuine Gear Case Oil 80W90, 12 x 1 Quart Case

**Eye/face protection** Safety glasses equipped with side shields are recommended as minimum protection in

industrial settings. If splashes are likely to occur wear tight fitting safety goggles and/or

Revision Date: 02-Jun-2017

face-shield.

**Skin protection** Wear protective gloves/clothing. Long sleeved clothing. Choose the appropriate protective

clothing / gloves based on the tasks being performed to avoid exposed skin surfaces.

Glove Type: Neoprene, Nitriles

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

General Hygiene Considerations Clean equipment, work area and clothing regularly. When using, do not eat, drink or smoke.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1. Information on basic physical and chemical properties

Appearance Brown / Clear

Physical State Liquid Odor Mild

Odor Threshold No information available

pH Not applicable
Melting point / melting range Not applicable

Boiling point / boiling range No information available

Flash Point  $> 180 \, ^{\circ}\text{C} \, / \, 356 \, ^{\circ}\text{F} \, \, \text{COC ASTM D92}$ 

Evaporation Rate

Flammability Limit in Air

Explosion Limits

No information available

Partition Coefficient (n-octanol/water)No information availableAutoignition TemperatureNo information availableDecomposing TemperatureNo information available

© 40C = 134.70 cSt; @ 100C = 16.36 cSt

**Other Information** 

#### 10. STABILITY AND REACTIVITY

10.1 Reactivity

Reactivity The product is chemically stable

10.2 Chemical stability

**Chemical Stability** Stable under recommended storage conditions.

10.3 Possibility of Hazardous Reactions

Possibility of Hazardous Reactions None under normal processing.

**Hazardous Polymerization**None under normal processing.

10.4 Conditions to Avoid

34055057-75000C020 - Honda Marine Genuine Gear Case Oil 80W90, 12 x 1 Quart Case

Revision Date: 02-Jun-2017

Conditions to Avoid Heat, flames and sparks.

10.5 Incompatible Materials

Incompatible Materials Strong oxidizing agents. Strong acids.

10.6 Hazardous Decomposition Products

Hazardous decomposition products

Thermal decomposition can lead to release of irritating gases and

vapors.

## 11. TOXICOLOGICAL INFORMATION

#### 11.1 Information on likely routes of exposure

**Inhalation** May cause irritation of respiratory tract.

**Eye contact** May cause slight irritation.

**Skin Contact** May cause an allergic skin reaction.

**Ingestion** May be harmful if swallowed.

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Olefin sulfide	= 6500 mg/kg (Rat)		
68937-96-2			
Phosphoric acid esters/amine salt	> 10,000 mg/kg		

# 11.2 Information on toxicological effects

Symptoms No information available

# 11.3 Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Not classified.

Serious eye damage/eye

irritation

Not classified.

**Sensitization** May cause an allergic skin reaction.

Mutagenic effects Not classified.

11.4 Carcinogenicity

Carcinogenicity No component of this product present at levels greater than or equal to 0.1% is identified as

a known or anticipated carcinogen by NTP, IARC, OSHA or ACGIH.

Legend:

NTP (National Toxicology Program) ACGIH (American Conference of Governmental Industrial Hygienists) IARC (International Agency for Research on Cancer) OSHA (Occupational Safety and Health Administration of the US Department of Labor)

Reproductive Effects Not classified.

STOT - single exposure Not classified.

STOT - repeated exposure Not classified

34055057-75000C020 - Honda Marine Genuine Gear Case Oil 80W90, 12 x 1 Quart Case

**Chronic Toxicity** Avoid repeated exposure.

Aspiration hazard Not classified.

11.5 Acute Toxicity

**Unknown acute toxicity** 9.50 % of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document.

Product Information (Estimated):

 ATEmix (oral)
 > 5,000 mg/kg

 ATEmix (dermal)
 > 2,000 mg/kg

 ATEmix (inhalation-dust/mist)
 > 5 mg/l

## 12. ECOLOGICAL INFORMATION

12.1 Ecotoxicity

Ecotoxicity effects No known significant effects or critical hazards. Plants and animals may experience harmful

or fatal effects when coated with petroleum products. Petroleum-based (mineral) lubricating oils normally will float on water. In stagnant or slow-flowing waterways, an oil layer can cover a large surface area. As a result, this oil layer might limit or eliminate natural atmospheric oxygen transport into the water. With time, if not removed, oxygen depletion in the waterway may be sufficient to cause a fish kill or create an anaerobic environment.

Revision Date: 02-Jun-2017

**Unknown aquatic toxicity** 16.06 % of the mixture consists of component(s) of unknown hazards to the aquatic

environment

12.2 Persistence and degradability No information available.

12.3 Bioaccumulation/Accumulation No information available

12.4. Mobility in soil No information available

PBT and vPvB assessment No information available

12.5 Other adverse effects: No information available

# 13. DISPOSAL CONSIDERATIONS

Hazard characteristic and regulatory waste stream classification can change with product use. Accordingly, it is the responsibility of the user to determine the proper storage, transportation, treatment and/or disposal methodologies for spent materials and residues at the time of disposition.

Waste Disposal Method This material, as supplied, is not a hazardous waste according to Federal regulations (40

CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local

regulations for additional requirements.

**Contaminated packaging** Dispose of in accordance with local regulations.

# 14. TRANSPORT INFORMATION

**DOT - Non bulk** Not regulated

<u>DOT - Bulk</u> Not regulated

IATA Not regulated

IMDG/IMO Not regulated

# 15. REGULATORY INFORMATION

# International Inventories

TSCA	All ingredients are on the inventory or exempt from listing		
DSL	All ingredients are on the inventory or exempt from listing		
NDSL	There are ingredients listed on the NDSL Inventory List		
ELINCS	Not Listed		
ENCS	All ingredients are on the inventory or exempt from listing		
CHINA	All ingredients are on the inventory or exempt from listing		
KECL	All ingredients are on the inventory or exempt from listing		
PICCS	All ingredients are on the inventory or exempt from listing		
AICS	All ingredients are on the inventory or exempt from listing		
NZIoC	All ingredients are on the inventory or exempt from listing		
REACH	All ingredients are on the inventory or exempt from listing		

# USA

# Federal Regulations

#### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

# SARA 311/312 Hazardous Categorization

Acute Health Hazard Skin Sensitizer
Chronic Health Hazard Skin Sensitizer

Fire Hazard No Sudden Release of Pressure Hazard No Reactive Hazard No

# **CERCLA/SARA 302 & 304**

Section 302 & 304 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 355.

Chemical Name	CAS No.	Weight-%	RQ	TPQ
Methyl methacrylate	80-62-6	<0.1	1000 lb final RQ	
			454 kg final RQ	
Cumene	98-82-8	<0.001	5000 lb final RQ	
			2270 kg final RQ	
Methylisobutylketone	108-10-1	< 0.0001	5000 lb final RQ	
			2270 kg final RQ	
Ethyl acrylate	140-88-5	< 0.0001	1000 lb final RQ	
			454 kg final RQ	

Toluene	108-88-3	<0.0001	1000 lb final RQ 454 kg final RQ	
Benzene	71-43-2	<0.00001	10 lb final RQ 4.54 kg final RQ	
Ethyl benzene	100-41-4	<0.00001	1000 lb final RQ 454 kg final RQ	

# Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

Chemical Name	CAS No.	Weight-%	HAPS data
Methyl methacrylate	80-62-6	<0.1	X
Cumene	98-82-8	<0.001	X
Methylisobutylketone	108-10-1	<0.0001	X
Ethyl acrylate	140-88-5	<0.0001	X
Toluene	108-88-3	<0.0001	X
Benzene	71-43-2	<0.0001	X
Ethyl benzene	100-41-4	<0.000001	X

## **CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CAS No.	Weight-%	U.S CWA (Clean Water Act)
Methyl methacrylate	80-62-6	<0.1	X
Toluene	108-88-3	<0.0001	X
Benzene	71-43-2	<0.0001	X
Ethyl benzene	100-41-4	<0.00001	X

# State Regulations

# **California Proposition 65**

This product can expose you to chemicals including, [Cumene, Methylisobutylketone, Ethyl acrylate, Toluene, Benzene and Ethyl benzene], which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Chemical Name	CAS No.	Weight-%	California Prop. 65		Safe Harbor Limits for Cancer-causing Chemicals (NSRLs)
Cumene	98-82-8	<0.001	Carcinogen		
Methylisobutylketone	108-10-1	<0.0001	Carcinogen Developmental		
Ethyl acrylate	140-88-5	<0.0001	Carcinogen		
Toluene	108-88-3	<0.0001	Developmental	7000µg/daylevel represents absorbed dose	
Benzene	71-43-2	<0.00001	Carcinogen Developmental Male Reproductive	24µg/dayoral 49µg/dayinhalation	6.4 μg/day oral 13 μg/day inhalation
Ethyl benzene	100-41-4	<0.000001	Carcinogen		54 μg/day inhalation 41 μg/day oral

#### State Right-to-Know

Chemical Name	CAS No.	New Jersey
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	X
Residual oils (petroleum), solvent dewaxed	64742-62-7	X
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	X
Petroleum distillates, hydrotreated light paraffinic	64742-55-8	X
Petroleum distillates, solvent dewaxed light paraffinic	64742-56-9	Х
Mineral oil	64742-53-6	X

New Jersey Worker and Community Right-to-Know Act:

Under the New Jersey Right-to-Know Act L. 1983 Chapter 315 N.J.S.A. 34:5A-1 et. seq., the product is to be identified as follows: PETROLEUM OIL (Lubricating Oil)

Canada

This material has been classified in accordance with the WHMIS 2015 regulation

Chemical Name	CAS No.	Weight-%	NPRI
Petroleum naphtha	64742-95-6	<0.1	Listed
Methyl methacrylate	80-62-6	<0.1	Listed
Cumene	98-82-8	< 0.001	Listed
Methylisobutylketone	108-10-1	< 0.0001	Listed
Ethyl acrylate	140-88-5	<0.0001	Listed
Toluene	108-88-3	< 0.0001	Listed
Benzene	71-43-2	< 0.00001	Listed
Ethyl benzene	100-41-4	<0.00001	Listed

Legend

NPRI - National Pollutant Release Inventory

# 16. OTHER INFORMATION

2 0

NFPA Health: 2 Flammability: 1 Instability: 0

Prepared By Lakyn Neumeyer

Revision Date: 02-Jun-2017

Revision Summary: New product number

## Disclaimer:

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of Safety Data Sheet**