

PRODUCT DESCRIPTION

A fast evaporating solvent which when added to specific paints improves drying in cold climates and facilitates spray application. * For use with most single part topside and antifouling paints

PRODUCT INFORMATION

Color	Y216
Specific Gravity	0.8675
Volume Solids	0%
Typical Shelf Life	3 yrs
VOC (As Supplied)	867 g/lt
Unit Size	1 US Pint 1 US Quart 1 US Gallon

DRYING/OVERCOATING INFORMATION

	Drying									
	Overcoating Substrate Temperature									
	41°F (5°C)		50°F (10°C)	73°F (23°C)		95°F (35°C)			
Overcoated By	Min	Max	Min	Max	Min	Max	Min	Max		
APPLICATION AND USE										
Method	Add small incre	ments, in acco	ordance with ind	ividual product	directions.					
Compatibility/Substrates	Compatible with most single part topside and antifouling paints.									
TRANSPORTATION, STORAGE A	ND SAFETY INFORM	IATION								
Storage	TRANSPORTATION: Special Thinner 216 should be kept in securely closed containers during transport and storage. STORAGE: Exposure to air and extremes of temperature should be avoided. For the full shelf life of Special Thinner 216 to be realised ensure that between use the container is firmly closed and the temperature is between 5°C/41°F and 35°C/95°F. Keep out of direct sunlight.									
Safety		oor ouring itt								
	DISPOSAL: Container Disposal: Triple Rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill or by other procedures approved by state or local authorities. GENERAL: Read the label safety section for Health and Safety Information, also available from our Technical Help Line.									
IMPORTANT NOTES	The performan LLC., including LLC. cannot gu FITNESS FOR SHALL NOT, U purchase of thi purchase price	surface prepa larantee this p A PARTICULA INDER ANY Cl s product, the	aration, proper a roduct's suitabi AR PURPOSE A IRCUMSTANCE buyer agrees th	ity for your part AND/OR MERC ES, BE LIABLE at the sole excl	environmental ticular purpose HANTABILITY FOR INCIDEN lusive remedy,	conditions. The or application. ARE EXCEEDE TAL OR CONSE if any, is limited	erefore, Interna IMPLIED WAR ED. Internationa EQUENTIAL DA	tional Paint RANTIES OF I Paint Inc. AMAGES. By		

Please refer to your local representative or visit http://www.yachtpaint.com for further information.

All trademarks mentioned in this publication are owned by, or licensed to, the AkzoNobel group of companies. © AkzoNobel 2014.

AkzoNobel