Page: 1

Revision: 12/21/2016

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Klean Strip Odorless Mineral Spirits

Reference #: SLM3616

Company Name: ScienceLab.com, Inc.

2700 Greens Rd., Bldg I, Ste 300

Houston, TX 77032

Web site address: (281)441-4400

Emergency Contact: https://www.sciencelab.com Chemtrec 1-800-424-9300

Intended Use: Paint, stain, and varnish thinning.

Synonyms: GKSP94006P, QKSP94005, QKSP94205, GKSP94006, GKSP94214

Additional Information This product is regulated by the United States Consumer Product Safety Commission

and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to

using the product.

2. HAZARDS IDENTIFICATION

Aspiration Toxicity, Category 1 Flammable Liquids, Category 3





GHS Signal Word: Danger

GHS Hazard Phrases: H304: May be fatal if swallowed and enters airways.

H226: Flammable liquid and vapor.

GHS Precaution Phrases: P233: Keep container tightly closed.

P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P280: Wear protective gloves/protective clothing/eye protection/face protection.

P240: Ground/bond container and receiving equipment.

P241: Use explosion-proof electrical/ventilating/lighting equipment. P243: Take precautionary measures against static discharge.

P242: Use only non-sparking tools.

GHS Response Phrases: P301+310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P331: Do NOT induce vomiting.

P370+378: In case of fire, use dry chemical to extinguish.

P303+361+353: IF ON SKIN (or hair): Remove/take off immediately all contaminated

clothing. Rinse skin with water/shower.

GHS Storage and Disposal

P405: Store locked up.

Phrases:

P501: Dispose of contents/container according to local, state and federal regulations.

P403+235: Store in cool/well-ventilated place.

Page: 2

Revision: 12/21/2016

Hazard Rating System:



Flammability Instability
Health O
NFPA: Special Hazard

HMIS:

OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

Potential Health Effects (Acute and Chronic):

Inhalation Acute Exposure Effects:

Vapor concentration may cause headache, dizziness, irritation of the respiratory tract, eye irritation, stupor, depression of the central nervous system, watering of the eyes, weakness, nausea, muscle twitches, and kidney effects. Aspiration into lungs may

cause pneumonia or death. Severe overexposure may cause convulsions,

unconsciousness, and death.

Skin Contact Acute Exposure Effects:

May cause irritation.

Eye Contact Acute Exposure Effects:

Liquid contact may cause irritation.

Ingestion Acute Exposure Effects:

Harmful or fatal if swallowed. May cause nausea, weakness, muscle twitches,

gastrointestinal irritation, diarrhea, unconsciousness, and death.

Chronic Exposure Effects:

Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage. Repeated or prolonged skin contact may cause redness, irritation, and scaling of the skin. May cause skin irritation, anemia, bone marrow damage, liver damage, and jaundice.

Medical Conditions Generally None known.

Aggravated By Exposure:

3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS # Hazardous Components (Chemical Name) Concentration RTECS #

64742-47-8 Hydrotreated light distillate (petroleum) 100.0 % OA5504000

4. FIRST AID MEASURES

Emergency and First Aid

Inhalation:

Procedures:

If user experiences breathing difficulty, move to air free of vapors. Administer oxygen or artificial respiration until medical assistance can be rendered.

Skin contact:

Wash with soap and large quantities of water for at least 15 minutes. Seek medical attention if irritation from contact persists.

Eye contact:

Immediately flush eyes with water, remove nay contact lens, continue flushing with water for at least 15 minutes. Get medical attention.

Ingestion:

Do not induce vomiting. Call your poison control center, hospital emergency room, or physician immediately.

GHS format

Page: 3

Revision: 12/21/2016

Signs and Symptoms Of

Primary routes of exposure:

Exposure:

Inhalation, ingestion, and dermal.

Note to Physician: Call your local poison control center for further instructions.

5. FIRE FIGHTING MEASURES

NFPA Class II

Flash Pt: > 105.00 F

Explosive Limits: LEL: 0.8 UEL: 6

Autoignition Pt: No data.

Suitable Extinguishing Media: Use carbon dioxide, dry chemical powder, or foam.

Fire Fighting Instructions: Self-contained respiratory protection should be provided for fire fighters fighting fires in

buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have

been exposed to intense heat or flame.

Flammable Properties and

No data available.

Hazards:

6. ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case

Material Is Released Or

Spilled:

Clean-up:

Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources,

keep flares, smoking or flames out of hazard area.

Small spills:

Take up the spilled liquid with sand, earth, or other noncombustible absorbent material

and place in a plastic container where applicable.

Large spills:

Dike far ahead of spill for later disposal.

7. HANDLING AND STORAGE

Precautions To Be Taken in

Handling:

Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty.

Dispose of empty container according to all regulations. Do not reuse this container.

Precautions To Be Taken in

Storing:

Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near flames or at elevated temperatures.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS # Partial Chemical Name OSHA TWA ACGIH TWA Other Limits

64742-47-8 Hydrotreated light distillate (petroleum) No data. TLV: 200 mg/m3 No data.

Respiratory Equipment

(Specify Type):

For OSHA controlled work place and other regular users. Use only with adequate ventilation under engineered air control systems designed to prevent exceeding

appropriate TLV. For occasional use, where engineered air control is not feasible, use properly maintained and properly fitted NIOSH approved respirator for organic solvent

vapors. A dust mask does not provide protection against vapors.

Eye Protection: Safety glasses, chemical goggles or face shields are recommended to safeguard against

potential eye contact, irritation, or injury. Contact lenses should not be worn while

working with chemicals.

Protective Gloves: Wear impermeable gloves. Gloves contaminated with product should be discarded.

GHS format

Revision: 12/21/2016

Promptly remove clothing that becomes soiled with product.

Various application methods can dictate use of additional protective safety equipment, Other Protective Clothing:

> such as impermeable aprons, etc., to minimize exposure. Before reuse, thoroughly clean any clothing or protective equipment that has been contaminated by prior use. Discard any clothing or other protective equipment that cannot be decontaminated, such

as gloves or shoes.

Engineering Controls (Ventilation etc.):

Use only with adequate ventilation to prevent build-up of vapors. Open all windows and doors. Use only with a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea, or eye-watering -- Stop -- ventilation is inadequate. Leave area immediately.

Work/Hygienic/Maintenance A source of clean water should be available in the work area for flushing eyes and skin.

Practices:

Do not eat, drink, or smoke in the work area.

Wash hands thoroughly after use.

9. PHYSICAL AND CHEMICAL PROPERTIES

[] Gas [X] Liquid **Physical States:** [] Solid

Colorless to light yellow Appearance and Odor:

Solvent odor

Melting Point: No data.

318.00 F - 354.00 F **Boiling Point:**

Autoignition Pt: No data. Flash Pt: > 105.00 F

LEL: 0.8 **Explosive Limits:** UEL: 6

Specific Gravity (Water = 1): 0.78 Vapor Pressure (vs. Air or No data.

mm Hg):

Vapor Density (vs. Air = 1): 5 Air = 1No data. **Evaporation Rate:** Solubility in Water: No data.

Solubility Notes: Very slightly soluble in cold water (<0.1% w/w)

100.0 % by weight. Percent Volatile: VOC / Volume: 780.0000 G/L

Additional Physical

Conductivity = <5 picosiemens/meter

Information

10. STABILITY AND REACTIVITY

Stability: Unstable [] Stable [X]

Conditions To Avoid -No data available.

Instability:

Incompatibility - Materials To Incompatible with strong oxidizing agents.

Avoid:

Hazardous Decomposition Or Thermal decomposition may produce carbon monoxide and carbon dioxide.

Byproducts:

Possibility of Hazardous Will occur [] Will not occur [X]

Reactions:

Conditions To Avoid -No data available.

Hazardous Reactions:

Page: 5

Revision: 12/21/2016

	\circ	COLOAL	INICODA	AATION
111 - 11		OGICAL	. INFORM	MAHON

Toxicological Information: Refer to section 2 for acute and chronic effects.

CAS# NTP **IARC ACGIH Hazardous Components (Chemical Name) OSHA**

Hydrotreated light distillate (petroleum) 64742-47-8 n.a. A4 n.a. n.a.

12. ECOLOGICAL INFORMATION

No data available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose in accordance with applicable local, state, and federal regulations.

14. TRANSPORT INFORMATION

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Paint Related Material, Not Regulated

DOT Hazard Class: UN/NA Number:

MARINE TRANSPORT (IMDG/IMO):

Paint Related Material IMDG/IMO Shipping Name:

EMS: F-E. S-E

UN Number: JUN1 **Packing Group:** Ш

Hazard Class:

IMDG MFAG Number:

IMDG EMS Page:

AIR TRANSPORT (ICAO/IATA):

ICAO/IATA Shipping Name: Paint Related Material

Packaging Instructions: See IATA Dangerous Goods Regulations

UN Number: 1263 Packing Group: Ш

Hazard Class:

Additional Transport

The shipper may apply one of the following exceptions: Combustible Liquid, Consumer Information: Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others,

as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to

ensure that subsequent shipments comply with these exceptions.

15. REGULATORY INFORMATION

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS# S. 302 (EHS) **Hazardous Components (Chemical Name)** S. 304 RQ S. 313 (TRI)

64742-47-8 Hydrotreated light distillate (petroleum) No No No

This material meets the EPA [X] Yes [] No Acute (immediate) Health Hazard 'Hazard Categories' defined [X] Yes [] No Chronic (delayed) Health Hazard

for SARA Title III Sections [X] Yes [] No Fire Hazard

311/312 as indicated: [] Yes [X] No Sudden Release of Pressure Hazard

[] Yes [X] No Reactive Hazard

Page: 6

Revision: 12/21/2016

CAS # Hazardous Components (Chemical Name)

Other US EPA or State Lists

64742-47-8 Hydrotreated light distillate (petroleum)

CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes -

Inventory; CA PROP.65: No

Regulatory Information

All components of this material are listed on the TSCA Inventory or are exempt.

Statement:

16. OTHER INFORMATION

Revision Date: 12/21/2016

Additional Information About No data available.

This Product:

Company Policy or

Disclaimer:

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and

local laws and regulations.