2.95A @ 12VDC 1.38A @ 24VDC



PRINT TO SCALE!

Flush Mount Maxillume - Flood Light

!NOTE! - This light requires proper ventilation - Ideally, place at least one vent .25" tall by 7" wide above and below the mounting position of the light.

	- — — — -	Cut for mounting template Mounting Template		
Cut Line Cut out the opening defined by the cut lines and pre drill the holes for the #6 self tapping screws Alignment	Alignment	Alignment		
		Cut Line		

Light circuits should be protected with an appropriately sized fuse. Each light draws approximately 2.95A at 12VDC and 1.38A at 24VDC. Fuses on circuits with multiple lights should be sized accordingly.

Limited Warranty

Lumitec is not responsible for product failure caused by abuse, neglect, improper installation, or failure in applications other than those for which it was designed, intended, and marketed

This product is warranted to be free from defects in workmanship and materials for a period of one year from the date of original purchase. Should your Lumitec product prove defective during the warranty period promptly notify Lumitec and return product with freight prepaid. Lumitec will, at its option, repair or replace the product without charge for parts or labor, or refund purchase price. Products repaired or replaced under this warranty shall be warranted for the unexpired portion of the warranty applying to the original product(s). Lumitec is not responsible for product failure caused by abuse, neglect, improper installation, or failure in applications other than those for which it was designed, intended, and marketed. No warranty or affirmation of fact, express or implied, other than as set forth in the limited warranty statement above is made or authorized by Lumitec. Any liability for consequential and incidental damages is expressly disclaimed. Lumitec liability in all events is limited to, and shall not exceed, the purchase price paid.