Product Safety Data Sheet	Document No.		
	Issue	01.09	
	Date Last Amended	October 2023	
	Last Amended by	MLN	ocean
Document Title	LB7P Lithium Battery PSDS		SIGNAL

Product Name: Lithium Battery Pack Type №: LB7P

For use with: RescueME PLB1

Chemistry: LiMnO₂ Total Weight: 51g Nominal Voltage: 9V

Construction: Battery containing three Energizer 123 cells connected in series

Lithium weight/cell: 0.55g Total lithium weight/battery: 1.65g

Section 1 - Manufacturer Information

Manufactured by: Ocean Signal Ltd., Unit 4, Ocivan Way, Margate, Kent, CT9

4NN, United Kingdom

Telephone number: +44 (0)1843 282930

Section 2 - Hazards Identification

This battery module is a self-contained unit. In this condition there are no hazards identified. Should the battery be damaged to cause leakage of the cell contents, the following hazards should be noted.

Ingestion: Swallowing the contents of a damaged battery can be harmfulInhalation: Contents of a damaged battery can cause respiratory irritation

Skin Contact: Contents of a damaged battery can cause irritation

Eye Contact: Contents of a damaged battery can cause severe irritation

Section 3 - Ingredients

Important Note: This battery should not be opened or burned. Exposure to the contents may be harmful.

Material or Ingredient	PEL (OSHA)	TLV (ACGIH)	%/wt.	
Lithium (CAS# 7439-93-2)	None Established	None established	<6	
Lithium Trifluoromethanesulfonate (CAS# 33454-82-9)	None Established	None Established	<3	
Lithium Trifluoromethanesulfonimide (CAS# 90076-65-6)	None Established	None Established	<3	
Manganese Dioxide (CAS# 1313-13-9)	5mg/m³ Ceiling (as Mn)	0.2mg/m³ TWA (as Mn)	<42	
1,2-Dimethoxyethane (CAS# 110-71-4)	None Established	None Established	<6	
1,3-Dioxolane (CAS# 646-06-0)	None Established	None Established	<8	
Propylene Carbonate (CAS# 108-32-7)	None Established	None Established	<8	
Carbon Black (CAS# 1333-86-4)	3.5mg/m³ TWA	3.5mg/m³ TWA	<1	

Ocean Signal Ltd. has issued this Product Safety Data Sheet to provide user advice on the above listed product(s). The information has been prepared in good faith and is believed to be accurate at the date of preparation. Ocean Signal Ltd. makes no warranty, either express or implied, with respect to this information.

Product Safety Data Sheet	Document No.		
	Issue	01.09	
	Date Last Amended	October 2023	
	Last Amended by	MLN	ocean
Document Title	LB7P Lithium Battery PSDS		SIGNAL

Material or Ingredient	PEL (OSHA)	TLV (ACGIH)	%/wt.	
Graphite (CAS# 7782-42-5)	15mg/m³ TWA (total dust) 5mg/m³ TWA (respirable fraction)	5mg/m³ TWA (respirable fraction	e <3	
Non Hazardous Components				
Steel (CAS#7439-89-6)	None Established	None Established	<20%	
Plastic and other	None Established	None Established	Remainder	

Section 4 - First Aid Measures

Ingestion: Seek medical advice. Do not induce vomiting or give food or drink.

Inhalation: Seek medical attention. Provide fresh air

Skin Contact: Remove any contaminated clothing and wash affected areas with soap

and water.

Eye Contact: Seek medical attention. Immediately flush eyes with water for a

minimum of 15minutes. Ensure that both upper and lower eyelids are

lifted during the flushing process.

Section 5 - Fire Fighting Measures

In case of fire involving lithium batteries, flood the area with water or smother with a class D fire extinguishing material suitable for lithium metal. (e.g. Lith-X)

Note: Water may not completely extinguish burning lithium batteries but will keep adjacent batteries cool reducing the risk of the fire spreading. As burning batteries will burn themselves out, flooding with water will control virtually all fires involving lithium batteries. However, the contents of lithium batteries will react with water to release hydrogen gas. In enclosed spaces this can cause an explosive mixture. Use a smothering agent in enclosed spaces which will extinguish burning lithium batteries.

Fire responders should wear self contained breathing apparatus. Burning lithium manganese dioxide batteries produce toxic and corrosive lithium hydroxide fumes.

Section 6 - Accidental Release Measures

Should batteries leak the following actions are recommended.

Ventilation: Keep room containing leaking lithium batteries well ventilated

Respiratory Protection: Avoid exposure to fumes from open or leaking batteries

Eye protection: Wear safety glasses with side shields when handling leaking

batteries

Gloves: Neoprene of natural rubber gloves should be worn when

handling leaking batteries

Storage: Leaking batteries should be stored in a leak proof container

Section 7 – Handling and Storage

Storage: Store in a cool, well ventilated area. Elevated temperature may result

in shortened battery life.

Ocean Signal Ltd. has issued this Product Safety Data Sheet to provide user advice on the above listed product(s). The information has been prepared in good faith and is believed to be accurate at the date of preparation. Ocean Signal Ltd. makes no warranty, either express or implied, with respect to this information.

Product Safety Data Sheet	Document No.		
	Issue	01.09	
	Date Last Amended	October 2023	
	Last Amended by	MLN	ocean
Document Title	LB7P Lithium Battery PSDS		SIGNAL

Handling: Avoid accidentally short-circuiting batteries. Prolonged short-circuiting

can cause the battery temperature to rise and significantly reduce

battery life.

Charging: These batteries are not designed for charging. Do not attempt to

recharge the battery. Recharging may result in cell venting or rupture.

Section 8 – Exposure Controls / Personal Protection

No special requirements are required for this battery under normal circumstances.

Section 9 - Physical and Chemical Properties			
Boiling Point at 760mm Hg (°C)	Not applicable for this item		
Vapour Pressure (mm Hg at 25°C)	Not applicable for this item		
Vapour Density	Not applicable for this item		
Density (g/cm³)			
Percent volatile by volume (%)	Not applicable for this item		
Evaporation Rate	Not applicable for this item		
Physical State	Solid		
Solubility in water	Not applicable for this item		
pH	Not applicable for this item		
Appearance and odour	Solid object / no odour		

Section 10 - Stability and Reactivity

No stability or reactivity issues identified

Section 11 – Toxicological Information

This battery module is not classified as hazardous waste. This battery module has been manufactured in accordance with the EU ROHS directive, 2011/65/EU.

Section 12 – Ecological Information

No ecological issues have been identified for this battery

Section 13 – Disposal Considerations

Dispose of battery module in accordance with applicable local regulations

Section 14 – Transport Information

This battery module has been tested in accordance with subsection 38.3 of part III of the UN Manual of Tests and Criteria. Summary test reports are available from Ocean Signal on request.

Ocean Signal Ltd. has issued this Product Safety Data Sheet to provide user advice on the above listed product(s). The information has been prepared in good faith and is believed to be accurate at the date of preparation. Ocean Signal Ltd. makes no warranty, either express or implied, with respect to this information.

Product Safety Data Sheet	Document No.		
	Issue	01.09	
	Date Last Amended	October 2023	
	Last Amended by	MLN	ocean
Document Title	LB7P Lithium Battery PSDS		SIGNAL

This battery module should be transported by air in accordance with the IATA dangerous goods regulations 64th edition, class 9, UN3090, proper name "Lithium metal batteries" and packed according to packing instruction 968 section II (<3) or section 1b (>2).

When supplied with equipment it is class 9, UN3091, proper name "Lithium metal batteries contained in equipment" and should be packed in accordance with packing instruction 970 section II.

The rescueME PLB1 can be taken on board passenger planes as carryon luggage for personal use under IATA regulation 2.3.5.9 (and Table 2.3.A).

The battery modules may be transported by road under special provision 188 of the ADR.

Section 15 Regulatory Information

No additional regulatory requirements are identified for this battery module.

Section 16 – Other

No information