

NMEA2000® Cable Adaptors



- NMEA2000® network standard
- Easy to Install
- Robust Design and Construction
- Waterproof to IP 67/68



Some marine manufacturers have based their networks on nonstandard connectors and we have a range of adaptors that can connect these networks to the standard cabling.

If the adaptor you need is not here please contact us as we may be able to produce it for you.

Please note that some engine manufacturers such as Suzuki, Volvo and Yamaha make their wiring the actual network backbone cable and in these cases the adapter cables end in a FEMALE socket to attach standard NMEA2000® devices to their backbone.



NMEA2000® Micro Cabling and Connectors

Micro Volvo/Suzuki Hub To NMEA2000 Micro Female Adaptor 3851 - F

Specifications	
Connector	PU
Female Pin	Copper, Alloy, Gold Plate
Screw Nut	Brass, Nickel Plated
Cable	PVC, 2x 24 AWG, 2x 22AWG + Drain, 30V, OD 6.00±0.15mm
IP	68

Yamaha Hub To NMEA2000 Female Socket Adaptor 3861 - F, 3862 - 0.2

Specifications	
Connector	PU
Female Pin	Copper, Alloy, Gold Plate
Screw Nut	Brass, Nickel Plated
Cable	PVC, 2x 24 AWG, 2x 22AWG + Drain, 30V, OD 6.00±0.15mm
IP	68

Micro Honda Outboard To NMEA2000 Male Connector 3852 - 1, 3852 - 3, 3852 - 6

Specifications	
Connector	PU
Female Pin	Copper, Alloy, Gold Plate
Screw Nut	Brass, Nickel Plated
Cable	PVC, 2x 24 AWG, 2x 22AWG + Drain, 30V, OD 6.00±0.15mm
IP	68

Raymarine E Series To NMEA2000 Male Adaptor 3853 - 1 Metre

Specifications	
Connector	PU
Female Pin	Copper, Alloy, Gold Plate
Screw Nut	Brass, Nickel Plated
Cable	PVC, 2x 24 AWG, 2x 22AWG + Drain, 30V, OD 6.00±0.15mm
IP	67

Oceanic Systems (UK) Ltd Unit 10-11 Milton Business Centre, Wick Drive, New Milton, Hampshire, BH25 6RH, United Kingdom

Tel: +44(0)1425 610022 Email: sales@osukl.com Fax: +44(0)1425 614794 Web: www.osukl.com Copyright © 2016 Oceanic Systems (UK) Ltd. All rights reserved. Our policy is one of continuous product improvement so product specifications are subject to change without notice. Oceanic Systems products are designed to be accurate and reliable. However, they should be used only as aids to vessel monitoring, and not as a replacement for traditional navigation and vessel monitoring techniques.