

Tree Anchors & Kits

Wire Rope

ISO 9001:2008 Certified Call 888-260-7444

Safety/Technical Info

Contact Us

Marine Products - Shackles

New Products

Clearance Items

Snap Shackles



Snap Shackle w/ Swivel Eye 316 Stainless

Customer Care/Info

Part	Size	WLL*	Net Wt	Dim	ensior	sions Package		Web Price	
Number	Size	(lbs.)	(lbs.)	A	В	C	Quantity	web File	
K-6-1	#1	600	0.14	2 3/4"	1/2"	1/2"	2	\$24.00	Add to cart
K-6-2	#2	1,200	0.28	3 1/2	5/8	5/8	2	\$31.00	Add to cart
K-6-3	#3	1,600	0.65	5 1/2	7/8	7/8	1	\$25.00	Add to cart



Snap Shackle - Fixed Eye 316 Stainless

Part	Size	WLL*	Net Wt	Din	nension	ns	Package	Web Price	
Number	3126	(lbs.)	(lbs.)	Α	В	C	Quantity	Web File	
K-7-1	#1	600	0.11	2 1/16"	1/2"	3/8"	2	\$22.00	Add to cart
K-7-2	#2	1,200	0.21	2 5/8"	5/8"	1 1/4"	2	\$29.00	Add to cart



Snap Shackle w/ Swivel Shackle 316 Stainless

Part Number	Size	WLL*	Net Wt	I	Dimensions		Package	Web Price	
rait Number	3126	(lbs.)	(lbs.)	A	В	C	Quantity	Web File	
K-8-1	#1	600	0.17	2 3/4"	1/2"	7/8"	2	\$28.00	Add to cart
K-8-2	#2	1,200	0.38	3 3/8"	5/8"	1 1/4"	2	\$36.00	Add to cart

Shackles



Standard "D" Shackle 316 Stainless

Our Stainless Steel Standard "D" Shackles are made with high corrosion resistance stainless steel. These Stainless Steel Standard "D" Shackles have a 5 to 1 WLL which rates our Standard "D" Shackle's WLL at 20% of its Ultimate Breaking Strength. The WLL is themaximum load that should ever be applied and is based on an in-line pull with no shockload. A

competent person should make an assessment of the conditions of use to determine the maximum load allowed. Our **Stainless Steel Standard "D" Shackle** has a screw pin which allows the pin to be removed from the body of the D Shackle.

Part	Size	WLL*	Net Wt	[Dimensions Packag		Package	Web Price	
Number	Size	(lbs.)	(lbs.)	A	В	C	Quantity	Web File	
K-10-06	3/16"	520	0.03	3/16"	7/16"	3/4"	10	\$31.00	Add to cart
K-10-08	1/4	760	0.06	1/4	1/2	13/16	10	\$36.00	Add to cart
K-10-10	5/16	1,380	0.16	5/16	5/8	1 1/8	5	\$28.00	Add to cart
K-10-12	3/8	2,000	0.24	3/8	13/16	1 3/8	5	\$33.00	Add to cart
K-10-16	1/2	3,000	0.40	1/2	15/16	1 5/8	5	\$48.00	Add to cart
K-10-20	5/8	5,600	0.97	5/8	1 1/4	2	1	\$25.00	Add to cart
K-10-24	3/4"	8000	1.61	3/4"	1-1/2"	2-7/16"	1	\$28.00	Add to cart
K-10-28	7/8"	9400	2.53	7/8"	1-3/4"	3"	1	\$43.00	Add to cart
K-10-32	1"	13000	3.60	1"	2"	3-3/32"	1	\$63.00	Add to cart



Long "D" Shackle

Part Number	Pin Size	WLL*	Net Wt	ı	Dimension	s	Package	Web Price	
rait Nullibei	FIII SIZE	(lbs.)	(lbs.)	A	В	C	Quantity	Web File	
K-12-06	3/16"	520	0.03	3/16"	7/16"	1 1/2"	10	\$38.00	Add to cart
K-12-08	1/4	760	0.06	1/4	1/2	1 3/4	10	\$42.00	Add to cart
K-12-10	5/16	1,380	0.16	5/16	5/8	2 5/16	5	\$36.00	Add to cart
K-12-12	3/8	2,000	0.24	3/8	13/16	2 7/8	5	\$51.00	Add to cart
K-12-16	1/2	3,000	0.40	1/2	15/16	3 1/2	1	\$24.00	Add to cart



Bow Shackle 316 Stainless

Our **316 Stainless Steel Bow Shackles** are made with high corrosion resistance stainless steel. These Stainless Steel Bow Shackles have a 5 to 1 WLL which rates our Bow Shackle's WLL at 20% of its Ultimate Breaking Strength. The WLL is the maximum load that should ever be applied and is based on an in-line pull with no shockload. A competent person should make an assessment of the conditions of use to determine the maximum load allowed. Our **Stainless Steel Bow Shackle** has a screw pin which allows the pin to be removed from the body of the Shackle.

Part	Pin Size	WLL*	Net Wt	I	Dimensions	3	Package	Web Price	
Number	FIII SIZE	(lbs.)	(lbs.)	A	В	C	Quantity	Web File	
K-14-06	3/16"	520	0.05	3/16"	7/16"	15/16"	10	\$36.00	Add to cart
K-14-08	1/4	760	0.07	1/4	1/2	1 1/8	10	\$42.00	Add to cart
K-14-10	5/16	1,380	0.15	5/16	5/8	1 1/2	5	\$32.00	Add to cart

K-14-12	3/8	2,000	0.28	3/8	13/16	1 3/4	5	\$42.00	Add to cart
K-14-16	1/2	3,000	0.53	1/2	15/16	2 1/8	1	\$20.00	Add to cart
K-14-20	5/8	5,600	1.22	1/2	15/16	3	1	\$24.00	Add to cart
K-14-24	3/4	8,00	2.06	1/2	15/16	3 1/8	1	\$36.00	Add to cart
K-14-28	7/8"	9400	2.85	7/8"	1-3/4"	3-3/8"	1	\$50.00	Add to cart
K-14-32	1"	13000	4.16	1"	2-1/4"	3-7/8"	1	\$72.00	Add to cart



Safety Bow Shackle 316 Stainless

Our 316 Stainless Steel Bow Shackles with a Safety Pin are made with high corrosion resistance stainless steel. This Safety Pinned Bow Shackle includes a Stainless Steel Safety Pin as an added measure which prevents the nut from detaching from the bolt, if it were to become loosened. These Stainless Steel Bow Shackles with a Safety Pin have a 5 to 1 WLL which rates our Bow Shackle's WLL at 20% of its Ultimate Breaking Strength. The WLL is the maximum load that should ever be applied and is based on an in-line pull with no shockload. A competent person should make an assessment of the conditions of use to determine the maximum load allowed. Our Stainless Steel Bow Shackle has a screw pin which allows the pin to be removed from the body of the Shackle as well as a Safety Pin to keep the nut and bolt in place.

Part	Pin Size	Bin Size		ı	Dimension	5	Package	Web	
Number	FIII SIZE	(lbs.)	(lbs.)	A	В	C	C Quantity	Price	
K-15-10	5/16"		0.21	5/16"	.46"	1.18"	4	\$20.00	Add to cart



Twisted Shackle 316 Stainless

Part Number	Pin Size	WLL*	Net Wt	D	imensions	1	Package	Web Price	
rait Nullibei	FIII SIZE	(lbs.)	(lbs.)	A	В	C	Quantity	Web File	
K-16-06	3/16"	520	0.05	3/16"	7/16"	7/8"	10	\$36.00	Add to cart
K-16-08	1/4	760	0.07	1/4	1/2	1 1/16	5	\$32.00	Add to cart
K-16-10	5/16	1,380	0.15	5/16	5/8	1 5/16	5	\$34.00	Add to cart
K-16-12	3/8	2,000	0.30	3/8	13/16	1 3/4	2	\$22.00	Add to cart
K-16-16	1/2	3,000	0.49	1/2	15/16	2 3/8	2	\$26.00	Add to cart

U.S. Rigging Supply • 4001 W. Carriage Drive, Santa Ana, CA 92704 • Tel. (714) 545-7444 • Fax (714) 545-3311

| Home | Anchors - Tree Guy | ANSI Products | Architectural Railing/Cable Rail | Cable & Cable Assemblies | Fiber Ropes | Fiddle Block & Flip Lines |
| Gripples | Halyard Kits | Hardware - Climbing, Safety, Marine and Rigging | KONG Products | Swage Sleeves - Oval & Stop Sleeves | Tools | Wire Rope |

