

C-LEVEL, INC.

A Division of Infinity Products, Inc.

141 Casco Drive ~ Avon, IN 46123 ~ 800-998-8683

3-Point TOWING-BRIDLE

For Inflatable Boats and Dinghies

Your Towing-Bridle comes completely assembled and ready to use. The 3-Point Towing-Bridle is designed for Inflatable boats and tenders the have (2) towing rings and (1) bow eye.

Here are some tips for the proper use and attachment of your new 3-Point Towing-Bridle:

1. Snap the two stainless steel 'snap hooks' from the non-adjustable legs to the Towing Eyes on the bow of the dinghy.
2. Snap the stainless steel 'snap hook' from the adjustable leg to the center bow eye. Adjust the leg to ensure even pulling with the (2) non adjustable legs.
3. Next, a Towing Line must be rigged to run from the port stern cleat, through the stainless Towing Ring (at the opposite end of the snap hook legs), and back to the starboard stern cleat.
4. At the Towing Ring on the Bridle, secure the line with a knot – then run each end of the towing line to the aft corner cleats as described above. This will prevent the dinghy from continual sliding on the ring while under tow.
5. After affixing the Towing Line to the two stern cleats, you will have formed an 'X-shaped' bridle of this Towing-Bridle and your towing line. By towing in this fashion, the Inflatable will track straighter and safer than with a single towing line led to a single towing ring on the bow.
6. The preferred distance to tow an inflatable or tender is 1 to 1 1/2 boat lengths behind the mother ship. As you slow down, the yellow float will prevent the bridle from sinking into the prop of the boat, but be vigilant of its location and if necessary haul in the towing line to shorten the distance to the inflatable or tender.

CAUTIONS: A) For added security while towing, a painter, tied from the dinghy bow to the mother ship and slightly slack, will serve as a lazy safety line. This practice is highly recommended for all towing situations.
B) Never tow a dinghy by the large lifting handle at the bow. Always attach the bridle to properly installed towing rings, and add a safety painter as mentioned above.

ZCL073

C-Level, Inc. Limited Warranty

C-Level, Inc. is a Division of Infinity Products, Inc.

C-Level, Inc. warrants that if used according to directions, this product will be free from defects in material and workmanship for a period of 12 (twelve) months from the date of its retail sale. This warranty shall be limited to the repair and, as necessary, replacement of parts, and any necessary labor and services required to repair or replace any parts, necessary to render the device free of defects. The sole obligation of C-Level shall be in the repair or replacement of this product, and under no circumstances shall C-Level, its agents, or successors, be liable for any direct, consequential or other incidental damages of any kind, however occasioned, whether by negligence or otherwise, or arising out of any claimed defect in the device or the method of its use.

THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, WETHER RELATING TO FITNESS, MERCHANTABILITY, OR OTHERWISE. Except as to the express warranty set forth above, the manufacturer DISCLAIMS any and all warranties and representations relating to the product.

Returns

To return your C-Level product, send it postage paid, with its original packaging and the original sales slip to the address below. Please include a return address and the exact reason for the return.

C-Level, Inc Returns
141 Casco Drive
Avon, IN 46123
800-998-8683

ZCL015