

Sew Clean® is the only safe and effective environmental solution to eliminate problematic clogs and nasty odors from black water systems

Sew Clean® builds upon the proven **Barnacle Buster®** formula and takes it one step further. Special attention has been given to ensure that foam and bacteria are significantly reduced while flushing. Like all of TRAC's products, **Sew Clean®** is non toxic, biodegradable and safe to use with all types of materials commonly found in black water systems.

Why use Sew Clean?

Sew Clean® is the most effective alternative when it comes to removing uric scale from deep inside black water systems. Formulated specifically to target uric scale and clean sewage systems from toilet to tank, **Sew Clean®** will dissolve clogs which cause plumbing to overflow and create nasty odors.

Sew Clean® has been designed to provide impeccable results without having to remove any piping or create a mess. **Sew Clean®** can be used by one of two methods:

- **Immersion:** Isolate the tanks, fill the entire system, and let stand for 24 hours.
- **Circulation:** Isolate the tanks, connect circulation equipment, and recirculate.

Sew Clean® is sold in concentrated form. One gallon of Sew Clean® will make 5 to 8 gallons of ready-to-use solution.
 (depending on dilution rates)

Availability

1 gallon , 5 gallon pail, 55 gallon drum
 or a 250 gallon tote tank

Safety

- When used as directed, **Sew Clean®** is non-corrosive to most metals commonly found in black water systems.
- **Sew Clean®** is biodegradable & can be disposed through regular sewer system.
- **Sew Clean®** is safe for your personnel.
- **Sew Clean®** passed the California Fish Toxicity Assay Test, Department of Hazardous Substances (Title 22) and complies with NSF International standard 60.
- Based on current EPA guidelines, **Sew Clean®** is classified as non-flammable and meets all requirements regarding hazardous and dangerous materials.



Pipe gallonage chart

Diameter Inches	Length in feet			
	1	5	10	20
1	0.04	0.2	0.4	0.8
2	0.16	0.8	1.6	3.2
3	0.37	1.84	4	8
4	0.65	3.26	7	13
5	1.02	5	10	20
6	1.47	7	15	29
7	2	10	20	40
8	2.61	13	26	52
9	3.31	16	33	66
10	4	20	41	82
12	6	29	59	118
14	8	40	80	160
16	10	52	104	208

FAST SAFE NON-TOXIC BIODEGRADABLE NON CORROSIVE NON HAZARDOUS

Dealer/Distributor Label

TRAC Ecological
 1103 Old Griffin Road, Ft. Lauderdale, FL 33004 USA
 001.954.987.2722 Voice ~ 001.954.583.4922 Voice
 001.954.583.4933 Fax
 www.TRAC-online.com ~ Info@TRAC-online.com

SEW CLEAN

Q. How Much Sew Clean Do I Use?

A. Starting with the highest head to the lowest head, add 1 quart of Sew Clean per head and flush each head once.

Q. How Long Should I Let Sew Clean Sit In My System?

A. The mixed solution should stay in the system for 6-12 hours, not to exceed 24 hours.

Q. Do I Need To Flush My System After Treatment?

A. Yes, flush each head a minimum of 10 times to remove any loosened residue.

Q. Can I Use Sew Clean With Other Sewage Additives?

A. No, Sew Clean should be used solely on its own. The black water tank will need to be pumped out and the sewage treatments replaced after each Sew Clean application.

Q. How Do I Clean My Holding Tank With Sew Clean?

A. To best determine the amount of Sew Clean needed to clean your holding tank, we would need to know the capacity of your tank. Sew Clean works best on tanks if diluted 4:1. Four parts water, one part Sew Clean. It is best if you try to flush your tank with water a couple of times before using Sew Clean as to first remove any loose waste. This way Sew Clean can go to work on the buildup directly on the tank walls.

Q. How Do I Use Sew Clean With A Vacuflush System?

A. First you will need to shut off your vacuflush system at the breaker. Add one quart of Sew Clean per head and flush. Let the mixed solution sit 6 to 12 hours then flush each head a few times. We recommend pumping the tank shortly after the process has been completed.

Q. Is Sew Clean Safe For A Septic System?

A. Sew Clean will by nature kill all bacteria that it comes in contact with however most often it is diluted far beyond the ability to do this once introduced into a septic tank. To be sure, you might want to flush some fresh septic enzymes a day or so after Sew Clean has been in your system.

Q. Can I Use Sew Clean In A Waterless Urinal?

A. Although Sew Clean was not intended for usage in waterless urinals and is not labeled as so, we've had some customers that have used it for this application with great results. The application consists of diluting the product to a 4:1 dilution ratio, filling and saturating the toilet for 4 to 8 hours, and then rinsing with fresh water. There are 3 main types of waterless urinals on the market at the moment and the one way valve systems work great with Sew Clean. For the Barrier Fluid urinals, the cartridge would need to be removed prior to the application as they often contain oil and that would affect the product negatively, and Microbiological urinals will need to have the microbial spores replenish once the application is completed. Also note that since uric scale is corrosive and can cause copper piping within the walls to fail fairly rapidly, so if said piping has not been upgraded when the waterless urinals were installed, using Sew Clean will cause it to clean said corrosion therefore making the problem worse, so please keep that in mind. Based on the size of most septic tanks, Sew Clean should not pose a threat.

Q. Will Trac's Solutions Attack By Gaskets, Seals Or Plastics?

A. NO! All of our solutions are specifically formulated for these types of applications. These materials can actually stay in full contact with the products for several weeks without being corrupted.