

Marine Air Heaters

New Air Top Evo 40 / 55 ▪ Air Top 2000 ST



Immediate Heat to Cabins and Compartments:

Webasto Marine Air Heaters provide a better solution to boaters who require the ultimate in compartment and cabin heating. Operating up to 20 hours on a single gallon of fuel, Webasto Marine Air Heaters are quiet and a powerful source of heat on any vessel. Webasto Air Heaters are available separately or as part of an all-inclusive Air Heater Kit.

The new Air Top Evo model offers greater comfort, safety and heating capacity for boats and yachts. Air heating ensures quick and efficient heating of cabins. Energy consumption and noise are significantly reduced by the new control system. Quick and easy installation makes the Air Top Evo an economical retrofit solution.

- Quiet operation
- Fresh-air or recirculated air-intake
- Sealed control electronics and connectors
- Precise electronic temperature control system to maintain a constant cabin temperature through stepless modulation
- Continuous heat output provides the exact temperature desired
- High air flow output due to powerful radial blower
- Very low electrical power and fuel consumption
- Robust composite casing, resistant to high temperature or salt
- Short heat up time
- Even distribution of warmth
- Space-saving installation and compact design
- Excellent opportunity to combine with BlueCool air conditioning systems
- Automatic altitude compensation as standard on Air Top Evo 40/55

Technical Specifications

Model	Air Top Evo 40	Air Top Evo 55	Air Top 2000 ST
Kits	5011417A (12V) 5011419A (24V)	5011420A (12V) 5011422A (24V)	5000699E (12 V)
Kit without Ducting	5011418A (12V)	5011421A (12V)	5001145C (12 V)
Heater Only	9027980B (12V) 9027981B (24V)	9027983B (12V) 9027986B (24V)	9014839C (12 V)
Heating Capacity	5,100 – 12,000 / 13,650 Btu (1.5 – 3.5 / 4.0* kW)	5,100 – 17,000 / 18,800 Btu (1.5 – 5.0 / 5.5** kW)	3,000 – 7,000 Btu (0.9 – 2.0 kW)
Fuel	Diesel		
Fuel Consumption	0.05 – 0.11 / 0.13 gal/h (0.18 – 0.43 / 0.49 l/h)	0.05 – 0.16 / 0.18 gal/h (0.18 – 0.61 / 0.67 l/h)	0.03 - 0.06 g/h (0.12 – 0.24 l/h)
Air Flow (against 0.5 bar) PLUS Mode	117.7 cfm (200 m ³ /h) 129.4 cfm (220 m ³ /h)	82.4 cfm (140 m ³ /h) 91 cfm (155 m ³ /h)	46 cfm (78 m ³ /h)
Rated Power Consumption	1.25 - 3.3 / 4.58 Amps (15 - 40 / 55 W)	1.25 - 7.9 / 10.8 Amps (15 - 95 / 130 W)	14 – 29 W
Net Weight	13 lbs (5.9 kg)	13 lbs (5.9 kg)	5.7 lbs (2.58 kg)
Dimensions (L x W x H)	16.7 x 5.8 x 6.4 in (423 x 148 x 162 mm)	16.7 x 5.8 x 6.4 in (423 x 148 x 162 mm)	12.5 x 4.78 x 4.84 in (318 x 122 x 123 mm)
Controller	Evo M Controller	Evo M Controller	SmarTemp Control 2.0

Kit Components:

- n Heater
- n Fuel Pump
- n Screen
- n Base Seal
- n Heater Wire Harness
- n Fuel Pump Harness
- n Fuel Line
- n Fuel Standpipe
- n Exhaust Tubing
- n Flexible Stainless Steel Exhaust pipe
- n Combustion Air Tubing
- n Flexible Ducting
- n Air Outlets
- n Operation/Installation Manual
- n 2 Year/2000 Hour Limited Warranty

Control Elements:



Webasto Thermo & Comfort
North America, Inc.

15083 North Road
Fenton, Michigan 48430
USA

Toll Free: 800-860-7866
Phone: 810-593-6000