



# TRIDENT MARINE®

## A1-15 EPA & CARB COMPLIANT FUEL LINE



### # 365 Series

**Trident Barrier Lined A1-15 Fuel Hose** for both gasoline (including ethanol blends) and diesel (including bio diesel blends). The #365 series exceeds ABYC H-24 & H-33, SAE J1527, ISO 7840, USCG Type A1-15; CARB Executive Order and EPA Certified low permeation Type A1-15; and is NMMA Type Accepted & CE certified. This hose is built with the best fuel, fire and age resistant formulation and a unique "Barrier Liner" on inside surface of the tube, so fuel is not in direct contact with rubber. Provides extraordinary resistance to fuel permeation, aging, and also to fire, heat, cold, and the ozone. Also provides excellent bend-ability.

### Specifications

#### Construction:

**Tube:** Nylon Internal Barrier, NBR

**Cover:** NBR/PVC Blend

**Reinforcement:** Polyester 2 spiral

**Temperature Range:** -20°F to 212°F (-28°C to 100°C)

**Lengths:** 250' (76 m), and 500' (152 m) **Reels,** 100' (30.5 m), 50' (15 m), and 25' (7.6 m) **Boxed**

Part Number	ID		OD		Burst Pressure		Working Pressure		Bend Radius		Weight		Permeation Rate
	in.	mm.	in.	mm.	psi	mpa	psi	mpa	in.	mm.	lb/100 ft	kg/m	Standard is 15g/m <sup>2</sup> /24 hrs (CE10)
365-0140	0.250	6.35	0.536	13.6	400	2.76	100	0.69	2.5	63.5	10.8	0.161	< 15
365-0560	0.312	7.92	0.611	15.5	400	2.76	100	0.69	2.5	63.5	13.3	0.198	< 15
365-0380	0.375	9.50	0.681	17.3	400	2.76	100	0.69	2.5	63.5	15.6	0.233	< 15
365-0120	0.500	12.7	0.821	20.9	400	2.76	100	0.69	4.5	114	20.5	0.306	< 15
365-0580	0.625	15.9	1.000	25.4	300	2.07	75	0.52	4.5	114	29.5	0.44	< 15
365-0340	0.750	19.0	1.130	28.7	200	2.07	75	0.52	4.5	114	34.0	0.505	< 15

**TRIDENT RUBBER INC.**

585 PLUM RUN ROAD  
CANONSBURG PA, 15317

**1-800-414-2628**

WWW.TRIDENTMARINE.COM