



Product No.	Description	A (in. [mm])	B (in. [mm])	C (in. [mm])	D (in. [mm])	E (in. [mm])	F (in. [mm])	G (in. [mm])	H (in. [mm])	I (in. [mm])	J (in. [mm])	Line Size	Working Load Limit (lb [kg])	Breaking Strength (lb [kg])	Weight (oz [g])
TY1405	H5	2.89 [73.3]	1.07 [27.3]	.22 [5.6]	1.44 [36.5]	.87 [22.0]	.63 [16.1]	.50 [12.6]	.88 [22.3]	.95 [24.1]	.26 [6.6]	5/16"-7/16" [8-11mm]	2,500 [1,130]	5,000 [2,270]	1.8 [52]
TY1505	H5 2:1	2.92 [74.1]	1.07 [27.2]	.22 [5.6]	1.44 [36.5]	.87 [22.0]	.63 [16.1]	.50 [12.6]	.88 [22.3]	.99 [25.1]	.26 [6.6]	5/16"-7/16" [8-11mm]	2,500 [1,130]	5,000 [2,270]	2.1 [61]
TY1408	H8	3.16 [80.2]	1.32 [33.5]	.28 [7.1]	1.50 [38.2]	.83 [21.2]	.76 [19.3]	.56 [14.3]	1.00 [25.4]	1.07 [27.1]	.31 [8.1]	3/8"-1/2" [10-12mm]	4,000 [1,810]	8,000 [3,630]	3.1 [87]
TY1508	H8 2:1	3.31 [84.1]	1.32 [33.5]	.28 [7.1]	1.50 [38.2]	.83 [21.2]	.76 [19.3]	.59 [15.0]	1.00 [25.4]	1.24 [31.5]	.32 [8.1]	3/8"-9/16" [10-14mm]	4,000 [1,810]	8,000 [3,630]	3.8 [109]
TY1508-S	H8 2:1 Split	3.31 [84.1]	1.32 [33.5]	.28 [7.1]	1.50 [38.2]	.83 [21.2]	.76 [19.3]	.59 [15.0]	1.00 [25.4]	1.24 [31.5]	.32 [8.1]	3/8"-9/16" [10-14mm]	4,000 [1,810]	8,000 [3,630]	3.8 [109]
TY1412	H12	3.74 [95.0]	1.50 [38.1]	.31 [7.9]	1.90 [48.3]	1.14 [29.0]	.88 [22.4]	.63 [15.9]	1.12 [28.4]	1.21 [30.7]	.38 [9.7]	7/16"-9/16" [11-14mm]	6,000 [2,720]	12,000 [5,440]	4.7 [132]
TY1512	H12 2:1	4.08 [103.6]	1.50 [38.1]	.31 [7.9]	2.00 [50.8]	1.25 [31.7]	.88 [22.4]	.66 [16.8]	1.12 [28.4]	1.44 [36.5]	.38 [9.7]	7/16"-5/8" [11-16mm]	6,000 [2,720]	12,000 [5,440]	6.3 [180]
TY1512-S	H12 2:1 Split	4.08 [103.6]	1.50 [38.1]	.31 [7.9]	2.00 [50.8]	1.25 [31.7]	.88 [22.4]	.66 [16.8]	1.12 [28.4]	1.44 [36.5]	.38 [9.7]	7/16"-5/8" [11-16mm]	6,000 [2,720]	12,000 [5,440]	6.3 [180]
TY1420	H20	4.84 [122.9]	1.84 [46.7]	.42 [10.7]	2.50 [63.5]	1.50 [38.1]	1.00 [25.4]	.75 [19.0]	1.50 [38.1]	1.58 [40.1]	.50 [12.7]	1/2"-5/8" [12-16mm]	10,000 [4,540]	20,000 [9,070]	10.5 [296]
TY1520	H20 2:1	5.25 [133.3]	1.84 [46.7]	.42 [10.7]	2.50 [63.5]	1.50 [38.1]	1.00 [25.4]	.88 [22.2]	1.50 [38.1]	1.80 [45.6]	.50 [12.7]	1/2"-3/4" [12-18mm]	10,000 [4,540]	20,000 [9,070]	13.5 [383]